



# P120i Card Printer



## Full Color Dual-Sided Card Printing at Single-Sided Printer Pricing



Now you can affordably take advantage of the space on the back of your cards. The Zebra P120i is the most affordable dual-sided, full color card printer in an industry-leading compact design. Ideal for space-constrained environments, Zebra's P120i brings you dual-sided printing at an unprecedented price.

### Compact and Flexible

- » The smallest footprint in its class - easily fits into a wide range of locations
- » Weighs less than 10 pounds (4.3 kg)
- » Conveniently fits on the desktop or under the counter
- » Print single-sided or dual-sided, color or monochrome

### Reliable Performance

- » Made with high strength plastics for reliability and lower maintenance costs
- » Integrated card feeder/flipper minimizes printer size while maximizing performance
- » Optional magnetic stripe encoding (HiCo/LoCo)

### Ideal for:

- » Employee ID cards
- » Student and faculty ID cards
- » Access control cards
- » Membership and loyalty cards
- » Personalized gift cards
- » Visitor ID cards

### Easy-to-Use

- » Intuitive design simplifies set-up and reduces training costs
- » LCD screen provides printer status and error messaging
- » Translucent card cover allows you to see when card supply is running low
- » Simple printhead replacement — no tools required!

### i Series™ Functionality

- » Automatic color optimization and driver configuration
- » Enhanced ribbon formulation for optimal color output
- » Ribbon image counter and ribbon low notification



### Load-N-Go Ribbon Cartridge

Load-N-Go™ ribbon cartridge with integrated card cleaning roller for easy ribbon replacement

# P120i



## Card Printer Product Specifications

### General Specifications

- » Integrated feeder-and-flipper
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-character LCD display
- » Windows® drivers for 2000 and XP (certified)
- » Two year printer warranty
- » Two year (unlimited passes) original printhead warranty

### Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 40 seconds per card full-color dual-sided (YMCKOK)\*
- » 30 seconds per card full-color single-sided (YMCKO)\*
- » 300 dpi (11.8 dots/mm) print resolution

\* Based on average print coverage per card.

### Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

### Card Specifications

- » Types: PVC, PVC Composite.
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 45 cards (30 mil)

### Communications Interface

- » USB 1.1 (USB 2.0 compatible) cable included
- » Optional built-in 10/100 Mbps Ethernet



Software drivers for the Zebra P120i Card Printer is tested to ensure that it meets Microsoft® standards for Windows® compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

### Ribbon Specifications

- » Load-N-Go ribbon cartridge with integrated card-cleaning roller
- » i Series™ ribbon intelligent technology
- » YMCKOK: 165 cards/cartridge
- » YMCKO: 200 cards/cartridge
- » Monochrome: 1000 cards/cartridge black, blue, red, green, gold, silver.  
850 cards/cartridge white
- » For optimum printer performance use Genuine Zebra Supplies



### Mechanical

- » Width: 7.9 in (201 mm)
- » Depth: 12.9 in (328 mm)
- » Height: 9.25 in (235 mm)
- » Weight: 9.5 lbs (4.3 kg)

### Electrical

- » 100 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 8MB image memory standard
- » FCC Class A, CE, UL, CUL, and CCC approved

### Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

### Options

- » Built-in 10/100 Mbps Ethernet
- » Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- » CardSense™ single-feed kit
- » Starter Kit (200 - 30 mil PVC cards and 1 YMCKOK ribbon)
- » Cleaning Kit (4 print engine and 4 feeder cleaning cards)

### Genuine Zebra Supplies

- » Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

[www.zebracard.com](http://www.zebracard.com)



Zebra Technologies Corporation



An ISO 9001 registered company ©2006 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P120i - 03/08

**North America**  
**Zebra Technologies Corporation**  
**Card Printer Solutions**  
1001 Flynn Road  
Camarillo, CA 93012-8706  
USA  
Telephone: +1 805 579 1800  
Fax: +1 805 579 1808  
Toll free in US: 800 452 4056  
e-mail: [cards@zebra.com](mailto:cards@zebra.com)

**Europe, Middle East, Africa**  
**Zebra Technologies Corporation**  
**Card Printer Solutions**  
The Valley Centre, Gordon Road  
High Wycombe  
Buckinghamshire HP13 6EQ, UK  
Telephone: +44 870 241 1527  
Fax: +44 870 241 0765  
e-mail: [eurosales@zebra.com](mailto:eurosales@zebra.com)

**Asia Pacific**  
**Zebra Technologies Corporation**  
**Card Printer Solutions**  
120 Robinson Road  
#06-01 Parakou Building  
Singapore 068913  
Telephone: +65 6858 0722  
Fax: +65 6885 0836  
e-mail: [asiasales@zebra.com](mailto:asiasales@zebra.com)

**Latin America**  
**Zebra Technologies Corporation**  
**Card Printer Solutions**  
9800 NW 41st Street, Suite 220  
Doral, FL 33178  
USA  
Telephone: +1 305 558 3100  
Fax: +1 305 558 8485  
e-mail: [latinsales@zebra.com](mailto:latinsales@zebra.com)